

UNIVERSAL CONNECTOR TSUC

QUICK & EASY INSTALLATION NEW SERIES

Quickly and Easily connect all types of wires of different sizes with this small splicing connector.

The TSUC "Universal Connector" is suitable for all types of Copper Conductors. (See product details)


The body of the connector comprises completely out of high quality Polyamid or rather Polycarbonat for the transparent version. The correct stripping lengths is easy to check through the integrated touch at each connector of this innovative series.

The tunnel-shaped entrance allows a good connection. A testing hole is located in front of the body and guarantee a optimal control inside.

- Suitable for all types of Copper conductors
- Nominal Voltage: 450V
- Rated Current: 24A
- Ambient Temperature: T110°C
- Self Extinguishing UL94V-2
- Different Sections per Connector
- Testing Hole in the Front
- The Rated Connecting Capacity: 0,2 - 4mm²

Tested For:

- ✓ VDE
- ✓ ENEC10
- ✓ Special Tests for Important Distribution





Connecting material
Connector with boltless contact points

Types:

TSUC 02N - 2 poles
TSUC 03N - 3 poles
TSUC 05N - 5 poles

Produktdetails:

Artikel	Antal Poler	Ø	Material	Färg	Förp	Förp/Kartong	
TSUC02N	2	0,2-4mm ²	PP	Transparent	100	60 Pack 6000 Styck/ Kartong	
TSUC03N	3	0,2-4mm ²	PP	Transparent	50	60 Pack 3000 Styck/ Kartong	
TSUC05N	5	0,2-4mm ²	PP	Transparent	25	60 Pack 1500 Styck/ Kartong	